

**Manuale d'uso - Efficienza Energetica / User Manual - Energy Efficiency / Manuel de l'utilisateur - L'efficacité énergétique / Handbuch - Energieeffizienz / Handboek - Energie-efficiëntie / Manual - Eficiencia Energética / Manual - Eficiência Energética / Manuell - Energieeffektivitet / Manuell - Energieeffektivitet / Manuaalinen - Energy Efficiency / Manual - Energieeffektivitet / Руководство - Энергоэффективность / Käsiiraamat - Energiatõhususe / Rokasgrāmata - Energoefektivitātes**

PF	PF										IT	EN	FR	DE	NL	ES	PT	SV	NO	DK	RU	ET	LV
<b>S</b>	<b>FABER</b>																						
<b>M</b>	110.0324.935 P0969																						
<b>AEchood</b>	68,7	kWh/a																					
<b>EEC</b>	B																						
<b>FDEchood</b>	27,01																						
<b>FDEC</b>	B																						
<b>LE</b>	77,3	lux/Watt																					
<b>LEC</b>	A																						
<b>GFE</b>	41,0	%																					
<b>GFEC</b>	G																						
<b>Qmin</b>	300	m <sup>3</sup> /h																					
<b>Qmax</b>	580	m <sup>3</sup> /h																					
<b>Qboost</b>	710	m <sup>3</sup> /h																					
<b>SPemin</b>	46	dB																					
<b>SPemax</b>	61	dB																					
<b>SPeboost</b>	65	dB																					
<b>PO</b>	0,85	Watt																					
<b>Ps</b>	0,0	Watt																					
			<b>PI</b>																				
<b>f</b>	1,0																						
<b>EElhood</b>	59,8																						
<b>Qbep</b>	392,0	m <sup>3</sup> /h																					
<b>Pbep</b>	444,0	Pa																					
<b>Qmax</b>	710	m <sup>3</sup> /h																					
<b>Wbep</b>	179,0	W																					
<b>WI</b>	2,2	W																					
<b>Emiddle</b>	170	lux																					
<b>Lwa</b>	61	dB																					

Vadovas - Energijos vartojimo efektyvumo / Manwal għall-Utent - Efficjenza fl-Energija / Kézi - Energiahatékonyás / Příručka - Energetická účinnost / Průručka - Energetická účinnost / Manual - Eficientă Energetică / Řečný - Efektivnost energetyczna / Priručnik - Energetska efikasnost / Navodilo - Energetska učinkovitost / Εγχειρίδιο - Ενεργειακή Αποδοτικότητα / Manuel - Enerji Verimliliği / Наръчник - Энергийна ефективност / Упутство - Энергетска ефикасност / Lámhleabhar Úsáideoir - Éifeachtúlacht Fuinnimh

PF FABER
S 110.0324.935 P0969
M 68,7 kWh/a
EEC B
FDEhood 27,01
FDEC B
LE 77,3 lux/Watt
LEC A
GFE 41,0 %
GFEC G
Qmin 300 m3/h
Qmax 580 m3/h
Qboost 710 m3/h
SPEmin 46 dB
SPEmax 61 dB
SPEboost 65 dB
P0 0,85 Watt
Ps 0,0 Watt
PI
f 1,0
EEIhood 59,8
Qbep 392,0 m3/h
Wbep 444,0 Pa
Qmax 710 m3/h
Wbep 179,0 W
WI 2,2 W
Emiddle 170 lux
Lwa 61 dB

Table with 15 columns: LT, MT, HU, CZ, SK, PL, HR, SL, GR, TR, BG, SR, GA. Each column contains technical specifications in the respective language. The first two columns (LT, MT) contain the product information, while the remaining 13 columns contain detailed technical data for different regions.